
Metrotile® Qube Prestige




Design



Overall Length	1305 mm
Length of Cover	1260 mm
Overall Width	350 mm
Width of Cover	321 mm
Minimum pitch	15° (27 %)
Maximum pitch	90°
Roof Cover	0.405 m ²
Tiles per m ²	2.47
Weight/panel	2.54 kg
Weight/area	6.27 kg/m ²

Material structure



- 1 Super durable powder coating (> 80 μm)
- 2 Polyurethane primer
- 3 Zinc-aluminium-magnesium alloy
- 4 Steel 0.60 mm
- 5 Zinc-aluminium-magnesium alloy
- 6 Polyester primer

Steel specification

The Metrotile Qube Prestige tile is made from pre primed zincaluminium-magnesium coated steel that when combined with the extra durable powder coating finish provides optimal performance. The grade of steel used is designed to allow pressing without cracking while at the same time is ridged enough to tolerate reasonable loads.

Steel Thickness	0.60 mm
Steel Grade	S280GD
Zinc-aluminium-magnesium Coating Mass	250 g/m ²
Zinc-aluminium-magnesium Coating Grade	ZM250

Coating specification

Polyester Powder Coating: The finish coating is an extremly durable High Gloss Polyester Powder Coating that is applied post pressing. This coating has proven durability retaining its high gloss finish for many years in all environments.

Polyurethane primer: The primer is applied by a coil coating process, this coating provides increased corrosion protection and a surface for superior adhesion of the Powder Coating that is applied.

Polyester Backer Coating: This coating provides increased durability to the underside of the tiles.

Colours

